

SMD High Current Inductor Size 2015

- Assemblage design, sturdy structure.
 -
 - Flat wire winding, achieve a low DC resistance.
- temperature and frequency range.

- High current DC/DC converter
-

Dimensions: [mm]







Land Pattern: [mm]

Electrical Properties:

[illegible]




Typical Electrical Characteristics:





Typical Electrical Characteristics:





Soldering Reflow:


Preheat condition: 150 ~200 °C/ 60~120 sec.

AI6 1.300011.329 ab ta12470C/ 60:120 s5c.

Packaging Information:


Tape Dimension :

Peel force of top cover tape:




The peel force of top cover tape shall be between 0.1 to 1.3 N

Reel Dimension: [mm]



Packaging Quantity:



100 Pcs/Reel



1 Reel /Inner box(100 Pcs)



3 Inner box/Carton box(300 Pcs)

Cautions and Warnings:

Storage Conditions:

- The storage period is within 12 months after the completion of production. Be sure to follow the storage conditions (temperature: -5 to 35°C, humidity: 75% RH Max).If the storage period elapses, the soldering of the terminal electrodes may deteriorate.The warranty period is one year.
- Product should not be exposed to environment with high temperature, high humidity, dust, corrosive gas and etc.
- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- Please always handle products carefully to prevent any damage caused by dropping down or inappropriate removing.

Operation Instructions:

- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Before soldering, be sure to preheat components.The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- Generally, Koher might not be familiar with either customer's specific application or actual requests as customer does.As a result customer shall be responsible for checking and confirming whether Koher product with the performance described in the product specification is suitable for using in customer's particular application or not.