


TLAR Series

Molding Power Inductors

Size 100760



FEATURES

- Higher current carrying Capacity, lower DCR, and more efficiency.
- Operating temperature: -55 to +125 °C(Including self - temperature rise).
- Quantity: 500PCS

APPLICATION


- AI Servers, Data Centers, GPU/AI Accelerators.
- Desktop Motherboards, CPU/GPU Power Delivery.
- Multi-phase VRM, High-current DC-DC Converters.
- Networking Equipment, Communication Infrastructure.

Dimensions: [mm]

Part Number		Inductance Tolerance	DC Resistance		Saturation Inductance		Temperature Rise		Weight
			DCR	DCR	L ₀	L ₀	ΔT	ΔT	
TLAR100760-85NM-02		85±20%				58		75	0.05
	2	85±20%				58		75	0.05


All test data is referenced to 25 °C ambient.
 Saturation Current will cause L0 to drop approximately 30%.
 Temperature Rise Current: The actual value of DC current when the temperature rise is ΔT=40 °C.

Soldering Reflow:



Packaging Information:

Tape Dimension:



A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
7.5±0.15	10.3±0.15	1.5±0.1	4.0±0.1	16.0±0.1	24.0±0.3	6.4±0.1	1.75±0.1	0.45±0.1

Product Marking:

Marking	Printing (Inductance)
---------	-----------------------

Reel Dimension: [mm]

Cautions and Warnings:

Storage Conditions :

-

Operation Instructions: